



(19)

(11) Publication number: **10267707 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **09072019**

(51) Intl. Cl.: **G01D 21/00 E02D 17/20 G01B 11/16**
G01C 7/02 G02B 6/00

(22) Application date: **25.03.97**

(30) Priority:

(43) Date of application
publication: **09.10.98**

(84) Designated contracting
states:

(71) Applicant: **HITACHI CABLE LTD**

(72) Inventor: **UCHIDA MASAHIKO**
TAMURA KIYOTOSHI
TOKUSHIMA AKIRA
MOTOKI KAZUhide

(74) Representative:

**(54) OPTICAL FIBER
SENSOR FOR DETECTING
TOPOGRAPHIC
DISPLACEMENT AND
LAYING METHOD FOR
THE SAME AND
TOPOGRAPHIC
DISPLACEMENT
DETECTING DEVICE
USING THE SAME**

(57) Abstract:

PROBLEM TO BE SOLVED: To provide an optical fiber sensor for detecting topographic displacement which has constant detecting sensitivity and which can specify a position where the topographic displacement is generated positively and a laying method of the same and a topographic displacement detecting device using the same.

SOLUTION: In an optical fiber sensor 6 for detecting topographic displacement to detect the topographic displacement from disconnection of an optical fiber 7 buried in a position to be the detecting position of topographic displacement, a linear member 10 which has designated strength is formed by previously hardening periphery of the optical fiber 7 with a solid material 9 and this linear member 10 is buried in a position to be the detecting position and the optical fiber 7 is disconnected by break of this linear member 10. The optical fiber 7 is disconnected when the linear member 10 is broken. Accordingly, detecting sensitivity becomes constant.

COPYRIGHT: (C)1998,JPO

